

SHRINE 4.1.0 Appendix A.7 - More Details: Shrine Configuration for SSO

`/opt/shrine/tomcat/lib/shrine.conf`, `/opt/shrine/tomcat/lib/override.conf`

`shrine.conf` and `override.conf`, located in Tomcat's `lib` directory, specify the behavior of the Shrine application. Configuration of Shrine SSO requires modifying the Shrine configuration files. You can make changes to either the `shrine.conf` file or the `override.conf` file. Once you have decided on which option to use, merge the sample config file into your existing Shrine configuration files:

Option 1:

add the following element under the top-level "shrine" element in `shrine.conf`

```
shrine {  
  
    ...  
  
    queryEntryPoint {  
  
        ...  
  
        authenticationType = "sso"  
  
        ...  
    }  
  
    ...  
  
    webclient {  
  
        ...  
  
        // ADJUST_FOR_YOUR_SITE  
        ssoLogoutUrl = https://[your hostname]/Shibboleth.sso/Logout?return=[your idP's logout URL]  
        sessionTimeout = "30 minutes"  
  
        ...  
    }  
  
    ...  
}
```

Option 2:

add the following to `override.conf`:

```
shrine.queryEntryPoint.authenticationType = "sso"  
  
# ADJUST_FOR_YOUR_SITE  
shrine.webclient.ssoLogoutUrl = https://[your hostname]/Shibboleth.sso/Logout?return=[your idP's logout URL]  
shrine.webclient.sessionTimeout = "30 minutes"
```

Next Step:

[SHRINE 4.1.0 Appendix A.8 - More Details: Using Authorization with SSO](#)